PRODUCT FAMILY / 12 SELECTION REFERENCES

DIN Rails & Mounting Rails

35 mm top-hat rails for compatible circuit breakers and control devices, plus compact and G-profile alternatives.



Illustrative category image; supplied configuration is confirmed at quotation.

PRODUCT OPTIONS

35 × 7.5 mm / 35 × 15 mm / 15 × 5.5 mm / G-profile / Slotted / solid

INCLUDE IN YOUR ENQUIRY

- Rail profile
- Width × height
- Material / finish
- Thickness
- Length and slot pattern

Explore options and prepare your enquiry online

youli-electric-global.vercel.app/components/din-rails/

MODEL & SPECIFICATION REFERENCES

DIN Rails & Mounting Rails

Select a reference and add quantity, material / finish, dimensions and the application requirements. Final supply is subject to quotation.

REFERENCE	CONFIGURATION	INFORMATION TO CONFIRM
35 × 7.5 mm / steel, galvanized / slotted / 2000 mm	35 × 7.5 mm mounting rail	steel, galvanized; slotted; reference length 2000 mm; confirm thickness and profile.
35 × 7.5 mm / steel, galvanized / solid / 2000 mm	35 × 7.5 mm mounting rail	steel, galvanized; solid; reference length 2000 mm; confirm thickness and profile.
35 × 15 mm / steel, galvanized / slotted / 2000 mm	35 × 15 mm mounting rail	steel, galvanized; slotted; reference length 2000 mm; confirm thickness and profile.
35 × 15 mm / steel, galvanized / solid / 2000 mm	35 × 15 mm mounting rail	steel, galvanized; solid; reference length 2000 mm; confirm thickness and profile.
35 × 7.5 mm / aluminium / slotted / 2000 mm	35 × 7.5 mm mounting rail	aluminium; slotted; reference length 2000 mm; confirm thickness and profile.
35 × 7.5 mm / aluminium / solid / 2000 mm	35 × 7.5 mm mounting rail	aluminium; solid; reference length 2000 mm; confirm thickness and profile.
35 × 15 mm / aluminium / solid / 1000 mm	35 × 15 mm mounting rail	aluminium; solid; reference length 1000 mm; confirm thickness and profile.
35 × 15 mm / aluminium / solid / 2000 mm	35 × 15 mm mounting rail	aluminium; solid; reference length 2000 mm; confirm thickness and profile.
35 × 7.5 mm / copper / solid / 2000 mm	35 × 7.5 mm mounting rail	copper; solid; reference length 2000 mm; confirm thickness and profile.
35 × 15 mm / copper / solid / 2000 mm	35 × 15 mm mounting rail	copper; solid; reference length 2000 mm; confirm thickness and profile.
15 × 5.5 mm / steel, galvanized / slotted / 2000 mm	15 × 5.5 mm mounting rail	steel, galvanized; slotted; reference length 2000 mm; confirm thickness and profile.
G32 × 15 mm / aluminium / solid / 2000 mm	G32 × 15 mm mounting rail	aluminium; solid; reference length 2000 mm; confirm thickness and profile.

Check the device clip against the selected rail profile. The 15 mm and G-profile references are alternatives for compatible devices, not substitutes for every 35 mm circuit-breaker rail.