PRODUCT FAMILY / 14 SELECTION REFERENCES

Selector Knobs & Switches

Panel-mounted rotary operators, selector heads and illuminated control switches.



Illustrative category image; supplied configuration is confirmed at quotation.

PRODUCT OPTIONS

Maintained / Spring return / Key operated / Illuminated / Head only

INCLUDE IN YOUR ENQUIRY

- Panel cut-out
- Positions / return action
- Contact arrangement
- LED voltage
- Head or complete assembly

Explore options and prepare your enquiry online

youli-electric-global.vercel.app/components/selector-knobs/

MODEL & SPECIFICATION REFERENCES

Selector Knobs & Switches

Select a reference and add quantity, material / finish, dimensions and the application requirements. Final supply is subject to quotation.

REFERENCE	CONFIGURATION	INFORMATION TO CONFIRM
22 mm / 2-pos / head	Maintained selector head	Head only; black handle; contact block selected separately.
22 mm / 2-pos / 1NO	Maintained selector	1NO contact; specify terminal and bezel material.
22 mm / 2-pos / 1NO+1NC	Maintained selector	1NO + 1NC; verify contact state in each position.
22 mm / 2-pos / return head	Spring-return selector head	Head only; right-to-left return; contacts separate.
22 mm / 2-pos / return / 1NO	Spring-return selector	1NO; right-to-left return.
22 mm / 3-pos / 2NO	Maintained selector	2NO; centre position and contact diagram required.
22 mm / 3-pos / return / 2NO	Centre-return selector	2NO; spring return to centre from both sides.
22 mm / 2-pos / key head	Key selector head	Maintained; specify key withdrawal positions; contacts separate.
22 mm / 2-pos / green LED	Illuminated selector	24 V AC/DC LED; 1NO + 1NC; maintained.
22 mm / 2-pos / orange LED	Illuminated selector	24 V AC/DC LED; 1NO + 1NC; maintained.
22 mm / 2-pos / yellow head	Illuminated selector head	Head only; LED module and contacts selected separately.
22 mm / 3-pos / white head	Illuminated selector head	Maintained head; LED module and contacts separate.
22 mm / 3-pos / red head	Illuminated selector head	Maintained head; LED module and contacts separate.
22 mm / 3-pos / single return	One-side-return selector	2NO; specify maintained side and spring-return side.

A head-only option excludes contacts and lighting modules. NO/NC describes contact type; submit the position diagram to confirm the assembled switching sequence.